

ISSUED SEPTEMBER 2020 (VALID 5 YEARS FROM THE DATE OF ISSUE)

PRODUCT NAME: GalMax™ SG Silver 3-in-1 Galvanising Paint

Page 1 of 12

This revision issued September 2020

## SECTION 1: IDENTIFICATION OF THE MATERIAL AND SUPPLIER

<b>SUPPLIER</b>	CHEMTOOLS PTY LTD	<b>PHONE</b>	1300 738 250 (Business Hours)
<b>ADDRESS</b>	Unit 2, 14-16 Lee Holm Road ST MARYS NSW 2760	<b>FAX</b>	02 9623 3670
		<b>WEBSITE</b>	www.chemtools.com.au

<b>PRODUCT NAME</b>	GalMax™ SG Silver 3-in-1 Galvanising Paint		
<b>PART NUMBER</b>	CT-SG	<b>PRODUCT TYPE</b>	Rapid drying industrial paint
<b>PRODUCT USE</b>	Decorative paint used in the industrial/structural/shop fitting industries		
<b>CREATION DATE</b>	September 2020	<b>LASTEST REVISION DATE</b>	Refer to date of issue above

## SECTION 2: HAZARDS IDENTIFICATION

<b>Statement of Hazardous Nature</b>	Classified as HAZARDOUS according to the criteria of the globally harmonized System of classification and Labelling of Chemicals (GHS).
<b>SUSMP Classification</b>	Schedule 5
<b>ADG Classification</b>	Classified as DANGEROUS GOODS by the criteria of the Australian Code for the Transport of Dangerous Goods by Road Rail and the New Zealand NZS5433: Transport of Dangerous Goods on Land 1263, Paints (TOULENE, XYLENE, ISOHEXANE)
<b>UN Number</b>	3YE
<b>Hazchem Code</b>	II
<b>Packing Group</b>	DANGER
<b>GHS Signal Word</b>	
<b>GHS Pictograms</b>	



### HAZARDOUS CLASSIFCATIONS

Flammable Liquies	Category 2
Aspiration Hazard	Category 1
Specific Target Organ Toxicity (Single Exposure)	Cateryory 3 Narcotic Effects
Specific Target Organ Toxicity (repeated Exposure)	Category 2
Acute Toxicity Inhalation	Category 4
Acute Toxicity Dermal	Category 4
Skin Corrosion/Irritation	Category 2
Toxic to reproduction	Category 1A
Chronic Aquatic Toxicity	Category 2

**PRODUCT NAME: GalMax™SG Silver 3-in-1 Galvanising Paint****Page 2 of 12****This revision issued September 2020****HAZARD STATEMENTS**

H225	Highly flammable liquid and vapour
H302	Harmful if inhaled
H304	May be fatal if i swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H360	May damage fertility or the unborn child
H373	May cause damage to organs through prolonged and repeated exposure
H411	Toxic to aquatic life with long-lasting effects

**PREVENTION PRECAUTIONARY STATMENTS**

P102	Keep out of reach of children
P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep the container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating, lighting, and all other equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust, fumes, gas, mist, vapors, or spray.
P264	Wash hands, face, and all exposed skin thoroughly after handling.
P270	Do not eat, drink, or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective clothing, gloves, eye/face protection, and suitable respirator.
P391	Collect spillage.

**RESPONSE PRECAUTIONARY STATEMENTS**

P101	If medical advice is needed, have a product container or label at hand.
P301+P310	If SWALLOWED: immediately call a POISON CENTER or doctor.
P303+P361+P353	If ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Wash exposed skin or hair with plenty of soap and water/shower.
P304+P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P304+P340	If INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P308+P313	If exposed or concerned, get medical advice/attention
P312	Call a POISONS CENTER or doctor/physician if you feel unwell.
P331	Do NOT induce vomiting
P332+P313	If skin irritation occurs, get medical advice/attention

**POISONS INFORMATION CENTER: 13 1126 FROM ANYWHERE IN AUSTRALIA (0800 764 766 FROM NEW ZEALAND)**

P337+P313 If eye irritation persists, get medical advice/attention  
 P363 Wash contaminated clothing before reuse  
 P370+P378 In case of fire, use carbon dioxide or dry chemical foam for extinction

### STORAGE PRECAUTIONARY STATEMENTS

P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
 P403+P235 Store in a well-ventilated place. Keep cool.  
 P405 Store locked up.

### DISPOSAL PRECAUTIONARY STATEMENTS

P501 Dispose of contents/containers in accordance with local, regional, national, and international regulations

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### Ingredients:

Chemical Entity	CAS Number	PROPORTION
Xylene	1330-20-7	< 25%
Toluol	108-88-3	< 25%
Solvent naptha (petroleum), light aliphatic	64742-89-8	< 20%
Isohexane	73513-42-5	< 15%
Ethanol	64-17-5	< 10%
1-methyl-2-propanol acetate; PM Acetate	108-65-6	< 10%
Ethyl Benzene	100-41-4	< 10%
Other ingredients not considered to be hazardous rounding to 100%		

## SECTION 4: FIRST AID MEASURES

### General Advice

If poisoning occurs, contact a doctor or Poisons Information Centre (Australia 13 11 26, New Zealand 0800 764 766)

### Inhalation

Remove the source of contamination or move the victim to fresh air - to avoid becoming a casualty. Remove contaminated clothing and loose remaining clothing. Allow the patient to assume the most comfortable position and keep warm. Keep at rest until fully recovered. If breathing is labored and the patient is cyanotic (blue), ensure airways are clear and have a qualified person give oxygen through a facemask preferably on a doctor's advice. If breathing has stopped, apply artificial respiration at once. In the event of cardiac arrest, apply external cardiac massage. DO NOT allow the victim to move about unnecessarily. Seek immediate medical advice.

**PRODUCT NAME: GalMax™SG Silver 3-in-1 Galvanising Paint****Page 4 of 12****This revision issued September 2020****Skin Contact**

This material, or a component of the material, can be absorbed through the skin with resultant toxic effects. If skin or hair contact occurs, immediately remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre or a Doctor; for 15 minutes and transport to the Doctor or Hospital. For gross contamination, immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if the material is insoluble). For skin burns, cover with a clean, dry dressing until medical help is available. If blistering occurs, do NOT break blisters. If swelling, redness, blistering, or irritation occurs seek medical assistance.

**Eye Contact**

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Take care not to rinse contaminated water into the unaffected eye or onto the face. Take special care if the exposed person is wearing contact lenses. Obtain medical attention if irritation persists.

**Ingestion**

Immediately rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Immediately call POISONS CENTER or the Doctor

**Notes to Physician**

Treat symptomatically

**SECTION 5: FIRE FIGHTING MEASURES**

---

**Hazchem Code**

3YE

**Suitable Extinguishing Media**

If material is involved in a fire, use alcohol-resistant foam or dry agent (carbon dioxide, dry chemical powder)

**Specific Hazards**

Highly flammable liquid and vapor. May form flammable vapor mixtures with air. Flameproof equipment is necessary in an area where this chemical is being used. Nearby equipment must be earthed. Electrical requirements for the work area should be assessed according to AS3000. Vapor may travel a considerable distance to the source of ignition, and flashback. Avoid all ignition sources. All potential sources of ignition (open flames, pilot lights, furnaces, spark-producing switches electrical equipment, etc.) must be eliminated, both in and near the work area. DO NOT SMOKE

**Fire Fighting Further Advice**

Heating can cause expansion or decomposition leading to violent rupture of containers. If safe to do so, remove containers from the path of fire. Keep containers cool with water spray. On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapor of combustion or decomposition.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

<b>Small Spills</b>	Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapors or dust. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labeled containers or drums for disposal.
<b>Large Spills</b>	If safe to do so, shut off all possible sources of ignition. Clear area of all unprotected personnel. Slippery when spilled. Avoid accidents, clean-up, and the inhalation of vapors. Work up wind or increase ventilation. Contain prevent runoff into drains and waterways. Use absorbent (soil, sand, or other inert material) Use a spark-free shovel. Collect and seal in properly labeled containers or drums for disposal. If contamination of crops, sewers, or waterways has occurred advise local emergency services. It is advisable to have a relevant spill kit on hand.
<b>Dangerous Goods Initial Emergency Response Guide</b>	No. 16 (Toluene)

## SECTION 7: HANDLING AND STORAGE

<b>Handling</b>	Avoid eye contact and skin contact. Avoid inhalation of vapor, mist or sanding dust
<b>Storage</b>	Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Store locked up. Keep containers standing upright. Keep containers closed when not in use. Check regularly for leaks.

### DANGEROUS GOODS CLASSIFICATION

Dangerous Goods Class	Packing Group	UN Number	Hazchem Code	Poison Schedule (SUSMP)
3	II	1263	3YE	S5

Classified as Dangerous Goods by the criteria of the Australian Code for the Transport of Dangerous Goods by Road & Rail and the New Zealand NZS5433: Transport of Dangerous Goods on Land.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### NATIONAL OCCUPATIONAL EXPOSURE LIMITS

Chemical Entity	CAS Number	TWA (ppm)	TWA (mg/m3)	STEL (ppm)	STEL (mg/m3)	Notices
Toluene	-	50	191	150	574	SK

Isoheptanes	-	400	1640	500	2050	-
Xylene	-	80	350	150	655	-
Ethanol	-	1000	1880	Not Av	Not Av	-
1-Methoxy-2-propanol acetate	-	50	274	100	548	SK

As published by Safe Work Australia. TWA: The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit): The average airborne concentration over a 15-minute period which should not be exceeded at any time during a normal eight-hour workday.

SK Notice: Absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, the exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely and potentially exposed during product manufacture

**Biological Limit Values** As per the national Model regulations for the control of Workplace Hazardous Substances (Safe Work Australia), the ingredients in this material do not have a Biological Limit Allocated

**Engineering Measures** Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use only in well-ventilated areas. Use with local exhaust ventilation or while wearing an appropriate respirator. Vapour heavier than air - prevent concentration in hollows or sumps. Do NOT enter confined spaces where vapour may have collected

**Personal Protection Equipment** SAFETY SHOES, OVERALLS, SUITABLE APRONS, GLOVES, CHEMICAL GOGGLES, RESPIRATOR.

Wear safety shoes, overalls, suitable aprons, gloves, chemical goggles and respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

**Hygiene Measures**

Keep away from food, drink, and animal feeding stuff. When using, do not eat, drink, or smoke. Wash hands before eating, drinking, or smoking. Avoid contact with clothing. Avoid eye contact and skin contact. Avoid inhalation of vapor, mist, or aerosols. Ensure that eyewash stations and safety showers are close to the workstation location.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

<b>Form</b>	Liquid
<b>Colour</b>	Silver
<b>Odour</b>	Aromatic
<b>Solubility</b>	Insoluble in water
<b>Specific Gravity (20°C)</b>	1.1
<b>Relative Vapour Density (air = 1)</b>	1-3.1 (based on highest and lowest ingredient)
<b>Vapour Pressure (20°C)</b>	Nor Available
<b>Flash Point</b>	Not Available (4°C Toluene, 23-27°C Xylene)
<b>Flammability Limits (%)</b>	Not Available
<b>Auto Ignition Temperature (°C)</b>	Not Available (280-536°C based on highest and lowest major ingredient) (ASTM E-659)
<b>Melting Point/Range (°C)</b>	Not Available
<b>Boiling Point/Range (°C)</b>	56-110°C (based on highest and lowest ingredient)
<b>pH</b>	Not Applicable
<b>Viscosity</b>	Not Available
<b>Total VOC (g/Litre)</b>	Not Available

Typical values only. Consult individual ingredients specification sheet

## SECTION 10: STABILITY AND REACTIVITY

<b>Chemical Stability</b>	This material is thermally stable when stored and used as directed.
<b>Conditions to Avoid</b>	Elevated temperature and sources of ignition.
<b>Incompatible Materials</b>	Incompatible with oxidizing agents, Natural Rubber, Butyl Rubber, EPDM, Nitrile Rubber, and Polystyrene.
<b>Hazardous Decomposition Products</b>	Oxides of Carbon and Nitrogen, smoke, and other toxic fumes.
<b>Hazardous Reaction</b>	No known hazardous reactions.

## SECTION 11: TOXICOLOGICAL INFORMATION

### TOXICOLOGICAL INFORMATION

Isoheptanes: LD50, Oral, Rat: >2000mg/kg

**PRODUCT NAME: GalMax™SG Silver 3-in-1 Galvanising Paint**  
**Page 8 of 12**  
**This revision issued September 2020**

Xylene: Oral LD50: Rat 4300mg/kg. Dermal TClo: Rat (Inhal) LC50: 5000ppm/4hr

PGMA: Oral LD50: Oral: 8532 mg/kg (rat); Dermal: > 5000 mg/kg (rabbit). Dermal TCLo: LC50: 23.49 mg/m3 / 6hr (rat):  
 No signs of toxicity were seen during exposure or upon gross pathological examination.

No adverse health effects are expected if the product is handled per this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and over-exposure occurs are:

**ACUTE EFFECTS**

- Inhalation**                      Material may be an irritant to mucous membranes and the respiratory tract. Inhalation of vapor can result in narcotic effects, headaches, dizziness/drowsiness, nausea, and possible unconsciousness. Inhalation of high concentrations can produce central nervous system depression
- Skin Contact**                    Harmful in contact with skin. Can be absorbed through the skin with resultant toxic effects. Contact with skin will result in defatting, reddening, and irritation. The constant defatting of the skin may cause dermatitis. AUH 066 Repeated exposure may cause skin dryness or cracking. Open cuts, abraded, or irritated skin should not be exposed to this material.
- Ingestion**                        Swallowing can result in irritation of the mouth, throat, and gastrointestinal tract, nausea, vomiting, diarrhoea and abdominal pain. May cause lung damage if swallowed. Small amounts of liquid aspirated into the respiratory system during ingestion or vomiting may cause bronchopneumonia or pulmonary oedema. If symptoms of poisoning become evident, or you feel unwell, contact a Poisons Information Centre, or call a doctor at once.
- Eye contact**                    Will irritate the eyes. Symptoms may include stinging, reddening, and watering which may become copious. Lengthy exposure or delayed treatment may cause permanent damage.

**ACUTE TOXICITY**

- Inhalation**                      This material has been classified as a Category 4 Hazard. Acute toxicity estimate (based on ingredients): 10 – 20 mg/L.
- Skin Contact**                    This material has been classified as a Category 2 Hazard. Acute toxicity estimate (based on ingredients): 1,000 - 2,000 mg/Kg.
- Ingestion**                        This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): > 2,000 mg/Kg
- Corrosion/Irritancy**            Eye: This material has been classified as non-hazardous.  
Skin: This material has been classified as a Category 2 hazard (reversible effects on skin).
- Sesnitation**                    Inhalation: This material has been classified as not a respiratory sensitizer. May cause respiratory sensitization in sensitive individuals, producing asthma-like symptoms  
Skin: This material has been classified as a not a skin sensitizer
- Aspiration Hazards**            This material has been classified as an Aspiration Hazard Category 1. May be fatal if swallowed.



**PRODUCT NAME: GalMax™SG Silver 3-in-1 Galvanising Paint**

**Page 9 of 12**

**This revision issued September 2020**

<b>Specific Target Organ Toxicity (single exposure)</b>	This material has been classified as a Category 2 Hazard. Exposure via inhalation may result in irritation to the respiratory tract, harm to the unborn child, and damage to kidney and liver
<b>CHRONIC TOXICITY</b>	
<b>Mutagenicity</b>	This material has been classified as non-hazardous
<b>Carcinogenicity</b>	This material has been classified as non-hazardous. This product may contain up to 10% of ethylbenzene. IARC has evaluated ethylbenzene and classified it as a Possible Human Carcinogen (Group 2B) based on sufficient evidence of cancer in exposed humans
<b>Reproductive Toxicity (including via lactation)</b>	This material has been classified as a Category 1A Hazard. May damage fertility or the unborn child. Not recommended for contact/use by pregnant or lactating mothers.
<b>Specific Target Organ Toxicity (repeated exposure)</b>	Inhalation: Overexposure via inhalation may result in depression of the central nervous system. May damage the kidneys and liver. There is some evidence of hearing loss in rats. Solvent abuse and noise interaction in the workplace environment may cause hearing loss.
<b>Other Health Effects Information</b>	This material may accentuate any pre-existing skin conditions. Persons with pre-existing asthma, liver, kidney, central nervous system, and skin complaints should avoid unnecessary exposure to the product. Every effort to protect eyes, respiratory tract, and skin exposure should be taken, especially in these circumstances

## SECTION 12: ECOLOGICAL INFORMATION

<b>General Information</b>	Avoid contaminating waterways. Collect spillage. No information available on this material, however, information from the ingredient with the highest effect.
<b>Acute aquatic Hazard</b>	Toxic to aquatic life with long-lasting effects. Do not empty into drains and collect spillage. Acute toxicity estimate (based on ingredients): 1 – 10 mg/L. Isoheptanes: Fish – Expected to be toxic: 1 <LC/EC/IC50<=10mg/L. Aquatic Invertebrate – Expected to be toxic: 1 <LC/EC/IC50<=10mg/L. Algae – Expected to be toxic: 1 <LC/EC/IC50<=10mg/L. Microorganisms - Expected to be toxic: 1 <LC/EC/IC50<=10mg/L.
<b>Long-Term Aquatic Hazard</b>	This material has been classified as a Category 2 Chronic Hazard. Non-rapidly or rapidly degradable substances for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, acute toxicity estimate (based on ingredients): 1 – 10 mg/L.
<b>Ecotoxicity</b>	No information available.
<b>Persistence and Degradability</b>	No information available.
<b>Bioaccumulation Potential</b>	No information available.
<b>Mobility</b>	Some of the ingredients will float on water

## SECTION 13: DISPOSAL CONSIDERATIONS

### General Information

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see Section 8 of this SDS. If possible, material and its container should be recycled. If material or container cannot be recycled, dispose of in accordance with local, regional, national and international Regulations

## SECTION 14: TRANSPORT INFORMATION

### ROAD AND RAIL TRANSPORT

Classified as Dangerous Goods by the criteria of the Australian Code for the Transport of Dangerous Goods by Road & Rail and the New Zealand NZS5433: Transport of Dangerous Goods on Land.

<b>UN No.</b>	1263
<b>Dangerous Goods Class</b>	3
<b>Packing Group</b>	II
<b>Hazchem Code</b>	3YE
<b>Emergency Respose Guide No.</b>	16
<b>Proper Shipping Name</b>	PAINTS (TOLUENE , XYLENE, ISOHEXANE)
<b>Dangerous Goods Diamond</b>	



<b>Segregation Dangerous Goods</b>	Not to be loaded with explosives (Class 1), flammable gasses (Class 2.1), if both are in bulk, toxic gases (Class 2.3), spontaneously combustible substances (Class 4.2), oxidizing agents (Class 5.1), organic peroxides (Class 5.2), toxic substances (Class 6.1) infectious substances (Class 6.2) or radioactive substances (Class 7). Exemptions may apply.
------------------------------------	--

### MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by the sea.

<b>UN No.</b>	1263
<b>Dangerous Goods Class</b>	3
<b>Packing Group</b>	II
<b>Hazchem Code</b>	3YE
<b>Emergency Respose Guide No.</b>	16
<b>Proper Shipping Name</b>	PAINTS (TOLUENE , XYLENE, ISOHEXANE)
<b>Dangerous Goods Diamond</b>	



**PRODUCT NAME: GalMax™ SG Silver 3-in-1 Galvanising Paint**  
**Page 11 of 12**  
**This revision issued September 2020**

## AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulation for transport by air.

**UN No.** 1263  
**Dangerous Goods Class** 3  
**Packing Group** II  
**Hazchem Code** 3YE  
**Emergency Respose Guide No.** 16  
**Proper Shipping Name** PAINTS (TOLUENE , XYLENE, ISOHEXANE)  
**Dangerous Goods Diamond**



## SECTION 15: REGULATORY INFORMATION

**HSNO Group Standard** Surface Coatings and Colourants (Flammable) Group Standard 2006: HSR002662.  
**This material is not subject to the following international agreements:** Montreal Protocol (Ozone depleting substances) The Stockholm Convention (Persistent Organic Pollutants) The Rotterdam Convention (Prior Informed Consent) International Convention for the Prevention of Pollution from Ships (MARPOL)  
**This material is subject to the following international agreements:** Basel Convention (Hazardous Waste) Wastes from production, formulation and use of inks, dyes, pigments, paints, lacquers, varnish  
**This material/constituent(s) is covered by the following requirements:** The Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) established under the Therapeutic Goods Act (Commonwealth). All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

## SECTION 16: OTHER INFORMATION

### KEY/LEGEND

**ADG Code** Australian Code for the Transport of Dangerous Goods by Road and Rail (7th Edition)  
**AICS** Australian Inventory of Chemical Substances  
**CAS Number** Chemical Abstracts Service (Registry Number)  
**CO2** Carbon Dioxide  
**Hazchem Code** Emergency action codes of numbers and letters that provide information to emergency services, especially firefighters.  
**IARC** International Agency for Research on Cancer  
**KG** Kilograms  
**LC50** LC stands for Lethal Concentration  
**LD50** LD stands for Lethal Dose

PRODUCT NAME: GalMax™SG Silver 3-in-1 Galvanising Paint

Page 12 of 12

This revision issued September 2020

LT	Liters
N.O.S.	Not Otherwise Specified
NTP	National Toxicology Program (USA)
ppm	Parts per Million
STEL	Short-Term Exposure Limit
SUSMP	Standard for the Uniform Scheduling of Medicines & Poisons
SWA	Safe Work Australia, formerly ASCC and NOHSC
TLV	Threshold Limit Value
TWA	Time Weighted Average
UN Number	United Nations Number

This SDS is prepared in accordance with the Safe Work Australia (SWA) document, entitled: **Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice (February 2016)**.

This Safety Data Sheet (SDS) summarises our best knowledge of the Health and Safety Hazard information about this product, including how to safely handle and use the product in the workplace.

Each user must review this SDS in the context of how the product will be handled and used. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact **Chemtools Pty Ltd**, whereby we will attempt to obtain additional information from our suppliers.

Our responsibility for products sold is subject to our Terms and Conditions, a copy of which is sent to our customers and is also available upon request.

Copyright © Chemtools Pty Lt