

## **HOSES LAYFLAT**

## Heavy Duty Black Layflat Hose



Pre-made Hose Assemblies

**APPLICATION**: General purpose rubber covered layflat hose used for the transfer of water in the pump hire and civil construction industries, other applications include dewatering, temporary bypass lines, irrigation installations as well as pumping of sludge and liquid fertilizer.

**REINFORCEMENT**: High strength circular woven textile

braid INNER TUBE: Black nitrile

COVER: Black nitrile TEMPERATURE: -25°C to +80°C

**ADVANTAGES**:

Abrasion resistant.

• UV stabilised.

• Minimal friction loss.

Non-conductive.

· Batch tested.

• Crimped-OHS safety.

PART NO.	ID	WALL THICKNESS	MAX. WP	WEIGHT	BEND RADIUS	LENGTH	FITTED WITH
	mm	mm	psi	kg/m	mm	metres	
LFHBR10220F	102	2.0	150	0.45	1100	20	AL CAMLOCKS
LFHBR10250F	102	2.0	150	0.45	1100	50	AL CAMLOCKS
LFHBR102100F	102	2.0	150	0.45	1100	100	AL CAMLOCKS
LFHBR10220FB	102	2.0	150	0.45	1100	20	BAUERS
LFHBR102520FB	102	2.0	150	0.45	1100	50	BAUERS
LFHBR102100FB	102	2.0	150	0.45	1100	100	BAUERS