



Grade S Shackle Dee Type

- Conforms to AS 2741, Hot Dipped Gal body surface finished and powder-coated Pin.
- Proof tested to 2 times WLL, batch sampling minimum break test to 6 times WLL.
- Marking with WLL, size, manufacture ID, grade and batch number.
- Suitable for lifting applications.
- Test Certificates are available upon request.

• Grade S Shackle Dee Screw Type



• Grade S Shackle Dee Safety Type



DISCRIPTION

Dee Screw Code	Dee Safety Code	WLL(T)	DIMENSIONS(mm)					Dee screw Weight(KG)	Dee Safety Weight(KG)
			d	D	W	L	E		
SK0506	N/A	0.5	6	8	12	22	17	0.05	0.08
SK0508	N/A	0.75	8	10	13	26	21	0.07	0.12
SK0510	N/A	1	10	11	17	32	25	0.11	0.16
SK0511	N/A	1.5	11	13	18	37	27	0.18	0.23
SK0513	SK0613	2	13	16	21	41	33	0.31	0.44
SK0516	SK0616	3.2	16	19	27	51	40	0.56	0.79
SK0519	SK0619	4.7	19	22	32	60	48	1	1.18
SK0522	SK0622	6.5	22	25	37	71	54	1.52	1.88
SK0525	SK0625	8.5	25	29	43	81	60	2.18	2.78
SK0529	SK0629	9.5	29	32	46	90	67	2.85	3.87
SK0532	SK0632	12	32	35	52	100	76	4.13	5.26
SK0535	SK0635	13.5	35	38	57	113	84	5.73	6.94
SK0538	SK0638	17	38	41	60	124	92	7.19	8.79
SK0544	SK0644	25	44	51	73	146	110	12	14.99
SK0551	SK0651	35	51	57	83	171	127	17.12	20.65
SK0563	SK0663	55	63	70	105	203	152	38.5	41.05