DID YOU KNOW?

about our...





Panel Shims Concrete Full

PANEL SHIMS CONCRETE FULL PLASTIC / AS 3850.1

Part	Colour	Thickness	Length	Width	Pack Qty
		(mm)	(mm)	(mm)	
MPAPLF010150	Brown	1	150	100	50
MPAPLF020150	Blue	2	150	100	50
MPAPLF030150	Green	3	150	100	50
MPAPLF050150	Yellow	5	150	100	50
MPAPLF100150	Black	10	150	100	20
MPAPLF150150	Grey	15	150	100	20
MPAPLF200150	White	20	150	100	15

310000 A8550,1

1 mm



2 mm



3 mm



5 mm

APPLICATIONS

- Temporarily levels and aligns concrete panels in preparation for final attachment
- Space is then filled with grout, sealant or a cement mix
- Decking, cabinetry, door and window frames, and machinery weighing less than 20 tonnes



MARKINGS:

- WLL
- (Working Load Limit)
- Australian Standard
- Hobson markings



10 mm



15 mm



20 mm

FEATURES

- AS 3850.1 stamped onto every shim
- 20 tonne WLL stamped onto every shim
- Ribbed profile prevents slippage
- · Colour coded by thickness for easy selection
- High load strength

Disclaimer: while every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees disclaim all liability in respect to anything or the consequences of anything done or omitted regarding the whole or any part of this document. HEC product marking is the manufacturing mark of Hobson Engineering. HEC is a registered trademark of Hobson Engineering.

