

HOSES RUBBER

EXITFLEX® EF640 EPDM Water Suction & Delivery Hose



APPLICATION: The EXITFLEX® EF640 water suction and delivery hose is designed for the transfer of domestic or industrial water, light slurries or liquid manure. With an EPDM tube and cover this hose is ideal for use where a chemical resistant tube and cover is required.

REINFORCEMENT: High tensile textile cord with embedded steel wire helix.

INNER TUBE: Black smooth EPDM.

COVER: Black wrapped EPDM - abrasion and ozone resistant.

SAFETY FACTOR: 3:1

BRANDING: Black stripe, green lettering.

TEMPERATURE: -20°C to +80°C

ADVANTAGES:

- Good cold weather flexibility.
- Constant working pressure throughout the size range.
- Abrasion resistant cover.
- Wide range of diameters.

PART NO.	ID	NOM. OD	WORKING PRESSURE	WEIGHT	BEND RADIUS	LENGTH	FITTINGS
	mm	mm	PSI	KG/m	mm	meters	UNFITTED
RAWSD5120	51	61	150	1.5	600	20	AL CAMLOCKS
RAWSD512FCE	51	61	150	1.5	600	10	BAUERS
RAWSD10210FB	102	114	150	3.3	1140	10	BAUERS
RAWSD15210FB	152	166	150	6.7	1650	10	BAUERS
RAWSD10210FBFV	102	114	150	6.7	1140	10	BAUERS AND FOOT VALVE
RAWSD15210FBFV	152	166	150	6.7	1650	10	BAUERS AND FOOT VALVE