

## HOSES RUBBER

### EXITFLEX® EF663 FRAS Air/Water Delivery Hose

**APPLICATION:** The EXITFLEX® EF663 heavy duty FRAS air/water delivery hose is designed for the transfer of air, water and stone dust in underground mining applications.

**REINFORCEMENT:** High tensile textile cord.

**INNER TUBE:** Black smooth conductive NR/SBR.

**COVER:** Black wrapped conductive NBR/EPDM - abrasion, ozone and fire resistant.

**SAFETY FACTOR:** 4:1

**BRANDING:** Orange lettering.


**TEMPERATURE:** -20°C to +80°C

**STANDARD:**

- AS 2660 Class A - 20BAR (300PSI)
- AS 1180.10B
- AS 1180.13A

**ADVANTAGES:**

- Good cold weather flexibility.
- Large range of diameters.
- Excellent resistance to abrasion and atmospheric conditions.



PART NO.	HOSE SIZE		WORKING PRESSURE @ 20		WEIGHT KG/m	BEND RADIUS mm	LENGTH METRES	DESCRIPTION
	ID (mm)	OD (mm)	PSI	BAR				
FRAWBD1025SVCF	25	37	300	20	0.7	370	5	CRIMPED SHOULDER AND FEMALE CAMLOCK
FRAWBD1025SV	25	37	300	20	0.7	370	5	CRIMPED SHOULDERS EACH END
FRAWBD10210SV	25	37	300	20	0.7	370	10	CRIMPED SHOULDERS EACH END
FRAWBD10220SV	25	37	300	20	0.7	370	20	CRIMPED SHOULDERS EACH END